

Our architectural products feature Super Guard polyester gel coat on the finished surfaces. Super Guard produces a hard, smooth, porcelain-like surface that eliminates the need for painting or refinishing. We recommend the following steps to insure the continued beauty of your baptistry.

TO CLEAN UNIT AFTER INSTALLATION

- Use warm water and one of the stronger liquid detergents such as Soft Scrub or Mr. Clean.
- Stubborn stains such as paint or tar can be removed with turpentine, paint thinner, or acetone.
- Plaster can be removed by scraping with a sharpened soft wooden stick. Do not use metal scrapers, wire brushes, or other metal tools. A powder type detergent, such as Spic & Span, may be used dry on a damp cloth to provide mild abrasive action to any residual plaster.
- Dulled areas may be restored by rubbing with an automotive rubbing compound followed by a light application of liquid wax, such as Johnson's Jubilee.

REGULAR MAINTENANCE PROCEDURES

- After draining the baptistry, use a sponge mop or a squeegee to remove any standing water.
- Using a diluted liquid detergent, clean the interior surfaces of the baptistry.
- Dry with a soft cloth.
- Repeated waxing after normal cleaning will help maintain the luster of the finish.
- **Baptistry should be drained at least once a month, then cleaned and allowed to dry for a minimum of 24 hours.**

DO NOT USE ABRASIVE CLEANERS
ABRASIVE CLEANERS MAY SCRATCH AND DULL THE SURFACE

SUPERIOR FIBERGLASS, INC.

P.O. Box 1989
Jacksonville, TX 75766

800-527-8438 or FAX 903-586-7547
www.superiorfiberglass.com